



PowerBase XLP

Cabinet only, Multi-cooling



Fully integrated, pre-wired and factory configured system that reduces the installation time significantly.



The BESS that pays for itself by earning from electricity markets and saving cost through peak shaving and power boost.

BESS for energy- and power-demanding sites

The PowerBase XLP is a large scale high-power and capacity energy storage system. Designed for quick deployment on a steel skid with container-format footprint. It is easy to transport to new locations if needed.

Built for future-proof performance

Designed and manufactured in Europe. Combining robust engineering with high-quality components to deliver modular, scalable and reliable energy storage for critical applications and demanding environments.

Secure, connected, and compliant

Our 48V systems are built for always-on operation. Encrypted communications, secure remote access, and full GDPR compliance, enabling uninterrupted connectivity, real-time insight, and maximum ROI through value stacking.

Resilient by design, reliable in use

Pixii BESS feature built-in redundancy, active monitoring, and automated recovery protocols. This ensures secure operation even under failure or cyber threat, ideal for mission-critical energy storage needs.

Pre-wired, pre-configured

The base is designed for easy deployment. Cabinets can be shipped with batteries installed and come pre-wired, with a separate AC distribution cabinet to simplify installation and reduce on-site work.

Comprehensive Service Level Agreement (SLA) and support

Proactive maintenance, fast response, and certified installers help maximize uptime and extend lifespan. SLAs secure optimal performance and ROI throughout the system lifetime.

Scalable base with hybrid cooling

Supports up to 900 kW power and 2 MWh capacity. Battery section features active air-conditioned cooling, making it ideal for high-throughput or warm, demanding environments.

Highlights

- Pre-wired and pre-configured
- Dual-zone active cooling system
- Single-lift operation
- Galvanic isolation (AC-DC)
- European quality & GDPR compliance
- Safe ~48V installation and operation

Key functions

- Ideal for EV site load support
- Peak shaving
- Balance market participation
- Electricity market participation



9 x XLP aircon cabinets with up to 100kW power and 225kWh total capacity per cabinet

PowerBase XLP Cabinet only, Multi-cooling

AC specifications	
Grid connection type	TT / TN
Phase config. (grid)	3ph
AC voltage (-10/+15%)	400V
Nominal frequency (grid)	50Hz
Max. AC power (±2%) ¹	900kWp
Off-grid operation support	No
Generator backup support	No

1. The stated power and energy capacities are baseline, or nominal, values. Actual performance can vary and may be constrained by several factors, including the state of charge (SoC), state of health (SoH) of the system, as well as thermal conditions. Time limited boost power is possible. Contact Pixii for details.

DC specifications	
Installed capacity (max)	0kWh
Max. system capacity	2025.7kWh
Nominal DC voltage	~48V

Communication and connectivity	
Wired interfaces	Ethernet LAN, RS 485 (Modbus), Digital IO
Wireless interfaces	Wi-Fi hotspot (local AP), 4G (optional kit)
Internal comm. protocols	CAN bus, Modbus TCP/RTU
External comm. protocols	MQTT

Safety	
Ingress Protection (IP)	IP55
Protection class	I
Overvoltage category (OVC)	III
Max. short-circuit current	50kA
Min. required SC current	2kA

Operating conditions	
Operating environment	Outdoor
Thermal management ¹	Fan, Heater, Aircon
Operating amb. temp. range ²	-20 - +55°C
Operating relative humidity ³	5 - 95% NC
Max. operating altitude	2000m

1. Battery section is cooled via active air-conditioning, while the power conversion compartment (housing PixiiBox units) is fan cooled.
2. Derating from 45°C
3. Non-condensing.

Physical specifications	
Dimensions (HxWxD)(mm)	2528x6334x2380
Net. weight (cabinet only)	7972kg
Color	RAL 7035
Status indicator (type)	-
Max. batt. capacity (5U)	126
Installed PixiiBoxes	0
Max. PixiiBox capacity	324

Warranty and compliance	
Security and safety standards¹ IEC/EN 62040-1, IEC/EN 62109-1, IEC/EN 62109-2, IEC/EN 62477-1, RED (2014/53/EU) - Cybersecurity (effective Aug 2025), RPEQ: Mechanically certified for lifting	
Grid standards² AS/NZS 4777.2 (AU+NZ), EREC G99 (Type A & B) (UK), IEC/EN 50549-1 (Type A & B) (EU), VDE-AR-N 4105 (DE), VDE-AR-N 4110 - Pending (DE)	

EMC standards IEC/EN 61000-6-1, IEC/EN 61000-6-2, IEC/EN 61000-6-3, IEC/EN 61000-6-4	
--	--

Environment standards ETSI EN 300 019-2-1 (Class 1.2), ETSI EN 300 019-2-2 (Class 2.3), ETSI EN 300 019-2-3 (Class 3.2)	
---	--

Regional compliance Load Restraint Guide 2018 (AU)	
Warranty (years/cycles)³	See note

1. Note that certifications and compliance for Safety, Grid, EMC, and Environmental standards for the PowerBase are based on the individual BESS cabinets used in this base configuration.
2. Designed in accordance with the relevant national and international standards listed above. Certification to specific revisions available on request. Additional local requirements may apply. **System approval pending. Currently valid for PixiiBox.**
3. Warranty terms may vary based on your SLA agreement. Please review the [warranty document](#) for details.