



PowerBase XLP

Cabinet only, Multi-cooling



Fully integrated, pre-wired and factory configured system that reduces the installation time significantly.



The BESS that pays for itself by earning from electricity markets and saving cost through peak shaving and power boost.

BESS for energy- and power-demanding sites

The PowerBase XLP is a large scale high-power and capacity energy storage system. Designed for quick deployment on a steel skid with container-format footprint. It is easy to transport to new locations if needed.

Built for future-proof performance

Designed and manufactured in Europe. Combining robust engineering with high-quality components to deliver modular, scalable and reliable energy storage for critical applications and demanding environments.

Secure, connected, and compliant

Our 48V systems are built for always-on operation. Encrypted communications, secure remote access, and full GDPR compliance, enabling uninterrupted connectivity, real-time insight, and maximum ROI through value stacking.

Resilient by design, reliable in use

Pixii BESS feature built-in redundancy, active monitoring, and automated recovery protocols. This ensures secure operation even under failure or cyber threat, ideal for mission-critical energy storage needs.

Pre-wired, pre-configured

The base is designed for easy deployment. Cabinets can be shipped with batteries installed and come pre-wired, with a separate AC distribution cabinet to simplify installation and reduce on-site work.

Comprehensive Service Level Agreement (SLA) and support

Proactive maintenance, fast response, and certified installers help maximize uptime and extend lifespan. SLAs secure optimal performance and ROI throughout the system lifetime.

Scalable base with hybrid cooling

Supports up to 900 kW power and 2 MWh capacity. Battery section features active air-conditioned cooling, making it ideal for high-throughput or warm, demanding environments.

Highlights

- Pre-wired and pre-configured
- Dual-zone active cooling system
- Single-lift operation
- Galvanic isolation (AC-DC)
- European quality & GDPR compliance
- Safe ~48V installation and operation

Key functions

- Ideal for EV site load support
- Peak shaving
- Balance market participation
- Electricity market participation



9 x XLP aircon cabinets with up to 100kW power and 225kWh total capacity per cabinet

PowerBase XLP Cabinet only, Multi-cooling

AC specifications		Communication and connectivity		Warranty and compliance	
Grid connection type	TT / TN	Wired interfaces	Ethernet LAN, RS 485 (Modbus), Digital IO	Security and safety standards ¹	
Phase config. (grid)	3ph	Wireless interfaces	Wi-Fi hotspot (local AP), 4G (optional kit)	IEC/EN 62040-1, IEC/EN 62109-1, IEC/EN 62109-2, IEC/EN 62477-1, RED (2014/53/EU) - Cybersecurity (effective Aug 2025), RPEQ: Mechanically certified for lifting	
AC voltage (-10/+15%)	400V	Internal comm. protocols	CAN bus, Modbus TCP/RTU	Grid standards ²	
Nominal frequency (grid)	50Hz	External comm. protocols	MQTT	AS/NZS 4777.2 (AU+NZ), EREC G99 (Type A & B) (UK), IEC/EN 50549-1 (Type A & B) (EU), VDE-AR-N 4105 (DE), VDE-AR-N 4110 (DE)	
Max. AC power (±2%) ¹	900kWp	Safety		EMC standards	
Off-grid operation support	No	Ingress Protection (IP)	IP55	IEC/EN 61000-6-1, IEC/EN 61000-6-2, IEC/EN 61000-6-3, IEC/EN 61000-6-4	
Generator backup support	No	Protection class	I	Environment standards	
<i>1. The stated power and energy capacities are baseline, or nominal, values. Actual performance can vary and may be constrained by several factors, including the state of charge (SoC), state of health (SoH) of the system, as well as thermal conditions. Time limited boost power is possible. Contact Pixii for details.</i>		Overvoltage category (OVC)	III	ETSI EN 300 019-2-1 (Class 1.2), ETSI EN 300 019-2-2 (Class 2.3), ETSI EN 300 019-2-3 (Class 3.2)	
DC specifications		Max. short-circuit current	50kA	Regional compliance	
Installed capacity (max)	0kWh	Min. required SC current	2kA	Load Restraint Guide 2018 (AU)	
Max. system capacity	2025.7kWh	Operating conditions		Warranty (years/cycles) ³ See note	
Nominal DC voltage	~48V	Operating environment	Outdoor	<i>1. Note that certifications and compliance for Safety, Grid, EMC, and Environmental standards for the PowerBase are based on the individual BESS cabinets used in this base configuration.</i>	
		Thermal management ¹	Fan, Heater, Aircon	<i>2. Designed in accordance with the relevant national and international standards listed above. Certification to specific revisions available on request. Additional local requirements may apply. System approval pending. Currently valid for PixiiBox.</i>	
		Operating amb. temp. range ²	-20 - +55°C	<i>3. Warranty terms may vary based on your SLA agreement. Please review the warranty document for details.</i>	
		Operating relative humidity ³	5 - 95% NC		
		Max. operating altitude	2000m		
		<i>1. Battery section is cooled via active air-conditioning, while the power conversion compartment (housing PixiiBox units) is fan cooled.</i>			
		<i>2. Derating from 45°C</i>			
		<i>3. Non-condensing.</i>			
		Physical specifications			
		Dimensions (HxWxD)(mm) ¹	2544x6360x2642		
		Net. weight (cabinet only)	7972kg		
		Color	RAL 7035		
		Status indicator (type)	-		
		Max. batt. capacity (5U)	126		
		Installed PixiiBoxes	0		
		Max. PixiiBox capacity	324		
		<i>1. Depth includes aircon units. Footprint on ground: 2420mm</i>			